

30 x 113 mm



Training cartridge suitable for use in DEFA automatic cannon. It may be offered linked with the TP-T version, in different configurations.

TP

| NORMATIVE REFERENCE | PROJECTILE TYPE | PROJECTILE WEIGHT | VELOCITY AT 7.5 m ^{1 2} |
|---------------------|-----------------|-------------------|-----------------------------------|
| MIL-C-46578D | TARGET PRACTICE | 245 g / 3781 gr | 810 m/s / 2657 ft/s |
| ENERGY AT 7.5 m | CASE | WATERTIGHTNESS | SERVICE TEMPERATURE |
| 80372 J | STEEL | YES | -54°C to +52°C -65°F to +125°F |



Traced training cartridge suitable for use in DEFA automatic cannon. It may be offered linked with the TP version, in different configurations.

TP-T

| NORMATIVE REFERENCE | PROJECTILE TYPE | PROJECTILE WEIGHT | VELOCITY AT 7.5 m ^{1 2} |
|---------------------|------------------------|-------------------|-----------------------------------|
| MIL-C-46578D | TARGET PRACTICE TRACER | 245 g / 3781 gr | 810 m/s / 2657 ft/s |
| ENERGY AT 7.5 m | CASE | WATERTIGHTNESS | SERVICE TEMPERATURE |
| 80372 J | STEEL | YES | -54°C to +52°C -65°F to +125°F |



Armor-piercing incendiary operational cartridge. Suitable for use in DEFA cannon.

API

| NORMATIVE REFERENCE | PROJECTILE TYPE | PROJECTILE WEIGHT | VELOCITY AT 7.5 m ^{1 2} |
|---------------------|---------------------------|-------------------|-----------------------------------|
| MIL-C-46578D | ARMOR-PIERCING INCENDIARY | 275 g / 4244 gr | 780 m/s / 2559 ft/s |
| ENERGY AT 7.5 m | CASE | WATERTIGHTNESS | SERVICE TEMPERATURE |
| 83655 J | STEEL | YES | -54°C to +52°C -65°F to +125°F |



High explosive incendiary, self-destructive operational cartridge. Suitable for use in DEFA automatic cannon.

HEI-SD

| NORMATIVE REFERENCE | PROJECTILE TYPE | PROJECTILE WEIGHT | VELOCITY AT 7.5 m ^{1 2} |
|---------------------|--|-------------------|-----------------------------------|
| MIL-C-46578D | HIGH EXPLOSIVE INCENDIARY SELF-DESTRUCTIVE | 242 g / 3735 gr | 810 m/s / 2657 ft/s |
| ENERGY AT 7.5 m | CASE | WATERTIGHTNESS | SERVICE TEMPERATURE |
| 79388 J | STEEL | YES | -54°C to +52°C -65°F to +125°F |

¹ Temperature: 21°C (70°F) | ² Test Barrel Length: 1400 mm (55")