


12.7 x 108 mm



Heavy machine gun ball cartridge suitable for all 12.7 x 108 mm weapons. It may be offered linked with any trajectory-matched cartridges, such as Tracer, API and API-T, in different configurations.

BALL

| NORMATIVE REFERENCE | TIP IDENTIFICATION | PROJECTILE TYPE | PROJECTILE WEIGHT | VELOCITY AT 24 m |
|---------------------|--------------------|-----------------------------------|-----------------------------------|---------------------|
| CBC STANDARD | NONE | BALL | 42 g / 648 gr | 882 m/s / 2894 ft/s |
| ENERGY AT 24 m | CASE | SERVICE TEMPERATURE | SAFETY TEMPERATURE | BARREL TWIST |
| 16336 J | BRASS | -54°C to +52°C -65°F to +125°F | -54°C to +71°C -65°F to +160°F | - |



Heavy machine gun tracer cartridge, with full luminosity trace up to 1500 m from the muzzle, visible in both day and night. Suitable for all 12.7 x 108 mm weapons, it may be offered linked with any trajectory-matched cartridges, such as Ball, API and API-T, in different configurations.

TRACER

| NORMATIVE REFERENCE | TIP IDENTIFICATION | PROJECTILE TYPE | PROJECTILE WEIGHT | VELOCITY AT 24 m |
|---------------------|--------------------|-----------------------------------|-----------------------------------|-----------------------------|
| CBC STANDARD | RED | TRACER | 40 g / 617 gr | AS PER REFERENCE AMMUNITION |
| ENERGY AT 24 m | CASE | SERVICE TEMPERATURE | SAFETY TEMPERATURE | BARREL TWIST |
| ≥ 15558 J | BRASS | -54°C to +52°C -65°F to +125°F | -54°C to +71°C -65°F to +160°F | - |



Heavy machine gun armor-piercing incendiary cartridge. Suitable for all 12.7 x 108 mm weapons, it may be offered linked with any trajectory-matched cartridges, such as Ball, Tracer and API-T, in different configurations.

API

| NORMATIVE REFERENCE | TIP IDENTIFICATION | PROJECTILE TYPE | PROJECTILE WEIGHT | VELOCITY AT 24 m |
|---------------------|--------------------|-----------------------------------|-----------------------------------|-----------------------------|
| CBC STANDARD | ALUMINIUM | ARMOR-PIERCING INCENDIARY | 42 g / 648 gr | AS PER REFERENCE AMMUNITION |
| ENERGY AT 24 m | CASE | SERVICE TEMPERATURE | SAFETY TEMPERATURE | BARREL TWIST |
| ≥ 16336 J | BRASS | -54°C to +52°C -65°F to +125°F | -54°C to +71°C -65°F to +160°F | - |



Heavy machine gun armor-piercing incendiary tracer cartridge. Suitable for all 12.7 x 108 mm weapons, it may be offered linked with any trajectory-matched cartridges, such as Ball, Tracer and API, in different configurations.

API-T

| NORMATIVE REFERENCE | TIP IDENTIFICATION | PROJECTILE TYPE | PROJECTILE WEIGHT | VELOCITY AT 24 m |
|---------------------|--------------------|-----------------------------------|-----------------------------------|-----------------------------|
| CBC STANDARD | RED AND ALUMINIUM | ARMOR-PIERCING INCENDIARY TRACER | 40 g / 617 gr | AS PER REFERENCE AMMUNITION |
| ENERGY AT 24 m | CASE | SERVICE TEMPERATURE | SAFETY TEMPERATURE | BARREL TWIST |
| ≥ 15558 J | BRASS | -54°C to +52°C -65°F to +125°F | -54°C to +71°C -65°F to +160°F | - |