

30 x 113 mm



Training cartridge suitable for use in DEFA automatic cannon. It may be offered linked with the TP-T version, in different configurations.

TP

NORMATIVE REFERENCE	PROJECTILE TYPE	PROJECTILE WEIGHT	VELOCITY AT 7.5 m ^{1 2}
MIL-C-46578D	TARGET PRACTICE	245 g / 3781 gr	810 m/s / 2657 ft/s
ENERGY AT 7.5 m	CASE	WATERTIGHTNESS	SERVICE TEMPERATURE
80372 J	STEEL	YES	-54°C to +52°C -65°F to +125°F



Traced training cartridge suitable for use in DEFA automatic cannon. It may be offered linked with the TP version, in different configurations.

TP-T

NORMATIVE REFERENCE	PROJECTILE TYPE	PROJECTILE WEIGHT	VELOCITY AT 7.5 m ^{1 2}
MIL-C-46578D	TARGET PRACTICE TRACER	245 g / 3781 gr	810 m/s / 2657 ft/s
ENERGY AT 7.5 m	CASE	WATERTIGHTNESS	SERVICE TEMPERATURE
80372 J	STEEL	YES	-54°C to +52°C -65°F to +125°F



Armor-piercing incendiary operational cartridge. Suitable for use in DEFA cannon.

API

NORMATIVE REFERENCE	PROJECTILE TYPE	PROJECTILE WEIGHT	VELOCITY AT 7.5 m ^{1 2}
MIL-C-46578D	ARMOR-PIERCING INCENDIARY	275 g / 4244 gr	780 m/s / 2559 ft/s
ENERGY AT 7.5 m	CASE	WATERTIGHTNESS	SERVICE TEMPERATURE
83655 J	STEEL	YES	-54°C to +52°C -65°F to +125°F



High explosive incendiary, self-destructive operational cartridge. Suitable for use in DEFA automatic cannon.

HEI-SD

NORMATIVE REFERENCE	PROJECTILE TYPE	PROJECTILE WEIGHT	VELOCITY AT 7.5 m ^{1 2}
MIL-C-46578D	HIGH EXPLOSIVE INCENDIARY SELF-DESTRUCTIVE	242 g / 3735 gr	810 m/s / 2657 ft/s
ENERGY AT 7.5 m	CASE	WATERTIGHTNESS	SERVICE TEMPERATURE
79388 J	STEEL	YES	-54°C to +52°C -65°F to +125°F

¹ Temperature: 21°C (70°F) | ² Test Barrel Length: 1400 mm (55")