

30 x 173 mm



Traced training cartridge suitable for use in Bushmaster II Mk44 and Mauser MK30 weapon systems.

TP-T

NORMATIVE REFERENCE	PROJECTILE TYPE	PROJECTILE WEIGHT	VELOCITY AT 7.5 m ^{1 2}
PPF(NAAG)D (2010)0011	TARGET PRACTICE TRACER	380 g / 5864 gr	1080 m/s / 3543 ft/s
ENERGY AT 7.5 m	CASE	WATERTIGHTNESS	SERVICE TEMPERATURE
221616 J	STEEL	YES	-54°C to +52°C -65°F to +125°F



High explosive incendiary operational cartridge suitable for use in Bushmaster and Mauser MK30 weapon systems.

HEI

NORMATIVE REFERENCE	PROJECTILE TYPE	PROJECTILE WEIGHT	VELOCITY AT 7.5 m ^{1 2}
PPF(NAAG)D (2010)0011	HIGH EXPLOSIVE INCENDIARY	370 g / 5710 gr	1080 m/s / 3543 ft/s
ENERGY AT 7.5 m	CASE	WATERTIGHTNESS	SERVICE TEMPERATURE
215784 J	STEEL	YES	-54°C to +52°C -65°F to +125°F

¹ Temperature: 21°C (70°F) | ² Test Barrel Length: 3000 mm (118,1/9")

