

Training cartridge suitable for use in Mk19 Mod 3, H&K GMG and other Automatic Grenade Launchers. It may be offered linked with the TP-T version, in different configurations.

ACC.		
	40 74 8	

Traced training cartridge suitable for use in Mk19 Mod 3, H&K GMG and other Automatic Grenade Launchers. It may be offered linked with the TP version, in different configurations.

	_
т	п
	μ

TP-T

NORMATIVE

REFERENCE

AC/225 (LG/3 - SG/1) D/17 112 mm / 4.41 inch

FUZE

NORMATIVE REFERENCE	CARTRIDGE LENGTH	CARTRIDGE WEIGHT	MUZZLE VELOCITY
AC/225 (LG/3 - SG/1) D/17	112 mm / 4.41 inch	375 g / 5787 gr NOMINAL	242 m/s / 794 ft/s
FUZE		CAPABILITY	
-		TRAJECTORY MATCHING HE VERSIONS	

CARTRIDGE

WEIGHT

375 g / 5787 gr

ΝΟΜΙΝΔΙ

CAPABILITY

TRAJECTORY MATCHING HE VERSIONS

TRACE OF MINIMUM 7 SECONDS

MU77LF

VELOCITY

242 m/s / 794 ft/s

CARTRIDGE

LENGTH

40×53mm

High explosive operational cartridge with blast and fragmentation capabilities, providing a lethal radius of 5 meters. Suitable for use in Mk19 Mod 3, H&K GMG and other Automatic Grenade Launchers. It may be offered linked with the HEDP version, in different configurations.



High explosive operational cartridge with self-destruct capability with reliability over 99%. Projectile blast and fragmentation effect provides a lethal radius of 5 meters. Suitable for use in Mk19 Mod 3, H&K GMG and other Automatic Grenade Launchers. It may be offered linked with the HEDP-SD version, in different configurations.

11	
40×53n TP-DA	
23	

Modern training cartridge with highly visible impact signature, designed to provide realistic training exercises during daytime without risk of generating unexploded ordnance and range fires. Suitable for use in Mk19 Mod 3, H&K GMG and other Automatic Grenade Launchers. It may be offered linked with the TP-DM-T version, in different configurations.

TP-DM

NORMATIVE REFERENCE	CARTRIDGE LENGTH	CARTRIDGE WEIGHT	MUZZLE VELOCITY
AC/225 (LG/3 - SG/1) D/17	112 mm / 4.41 inch	375 g / 5787 gr NOMINAL	242 m/s / 794 ft/s
FUZE		CAPABILITY	
-		TRAJECTORY MATC VISUAL SIGNATURE UPON	



Modern traced training cartridge with highly visible impact signature, designed to provide realistic training exercises during daytime without risk of unexploded ordnance generation. Suitable for use in Mk19 Mod 3, H&K GMG and other Automatic Grenade Launchers. It may be offered linked with the TP-DM version, in different configurations.

TP-DM-T

NORMATIVE REFERENCE	CARTRIDGE LENGTH	CARTRIDGE WEIGHT	MUZZLE VELOCITY
AC/225 (LG/3 - SG/1) D/17	112 mm / 4.41 inch	375 g / 5787 gr NOMINAL	242 m/s / 794 ft/s
FUZE		CAPABILITY	
-		TRAJECTORY MATCHING HE VERSIONS VISUAL SIGNATURE UPON IMPACT (ORANGE CLOUD TRACE OF MINIMUM 7 SECONDS	



High explosive dual purpose operational cartridge provides simultaneously a lethal blast and fragment radius of 5 meters and armor penetration greater than 50 mm RHA. Suitable for use in Mk19 Mod 3, H&K GMG and other Automatic Grenade Launchers. It may be offered linked with the HE version, in different configurations.



High explosive dual purpose operational cartridge with self-destruct capability with reliability over 99%. Projectile blast and fragmentation effect provides a lethal radius of 5 meters and armor penetration greater than 50 mm RHA. Suitable for use in Mk19 Mod 3, H&K GMG and other Automatic Grenade Launchers. It may be offered linked with the HE-SD version, in different configurations.



ΔC.







٨C





NORMATIVE REFERENCE	CARTRIDGE LENGTH	CARTRIDGE WEIGHT	MUZZLE VELOCITY
AC/225 (LG/3 - SG/1) D/17	112 mm / 4.41 inch	375 g / 5787 gr NOMINAL	242 m/s / 794 ft/s
FUZE		CAPABILITY	
POINT-DETONATING		BLAST WITH FRAGMENTATION	

HE-SD

NORMATIVE REFERENCE	CARTRIDGE LENGTH	CARTRIDGE WEIGHT	MUZZLE VELOCITY
/225 (LG/3 - SG/1) D/17	112 mm / 4.41 inch	375 g / 5787 gr NOMINAL	242 m/s / 794 ft/s
FUZE		CAPABILITY	
POINT-DETONATING WITH SELF-DESTRUCT		BLAST WITH FRAGMENTAT	TION AND SELF-DESTRUCT

HEDP

NORMATIVE REFERENCE	CARTRIDGE LENGTH	CARTRIDGE WEIGHT	MUZZLE VELOCITY
C/225 (LG/3 - SG/1) D/17	112 mm / 4.41 inch	375 g / 5787 gr NOMINAL	242 m/s / 794 ft/s
FUZE		CAPABILITY	
POINT-DETONATING		BLAST WITH FR PENETRATE MINIMU	

HEDP-SD

NORMATIVE REFERENCE	CARTRIDGE LENGTH	CARTRIDGE WEIGHT	MUZZLE VELOCITY
C/225 (LG/3 - SG/1) D/17	112 mm / 4.41 inch	375 g / 5787 gr NOMINAL	242 m/s / 794 ft/s
FUZE		CAPABILITY	
POINT-DETONATING WITH SELF-DESTRUCT		BLAST WITH FRAGMENTATION AND SELF-DESTRUCT PENETRATE MINIMUM 50 mm RHA PLATE	

 $^{\rm 1}$ Temperature: 21°C (70°F) | $^{\rm 2}$ Test Barrel Length: 434 m (17")

